

Knowledge Base

HOW TO: Backup, Edit, and Restore the Registry in Windows 2000

PSS ID Number: 322755

Article Last Modified on 11/6/2003

The information in this article applies to:

- Microsoft Windows 2000 Server
 - Microsoft Windows 2000 Advanced Server
 - Microsoft Windows 2000 Professional
 - Microsoft Windows 2000 Datacenter Server
-

This article was previously published under Q322755

For a Microsoft Windows XP version of this article, see [322756](#).

For a Microsoft Windows NT 4.0 version of this article, see [323170](#).

For a Microsoft Windows 95, Windows 98, and Windows Me version of this article, see [322754](#).

IN THIS TASK

- [SUMMARY](#)
 - [How to Back Up the Registry](#)
 - [How to Export Registry Keys](#)
 - [How to Back Up the Whole Registry](#)
 - [How to Edit the Registry](#)
 - [How to Restore the Registry](#)
 - [How to Restore Registry Keys](#)
 - [How to Restore the Whole Registry](#)
- [REFERENCES](#)

SUMMARY

This step-by-step article describes how to back up, edit, and restore the registry in Windows 2000. Microsoft recommends that before you edit the registry, you back up the registry and understand how to restore it if a problem occurs.

[back to the top](#)

How to Back Up the Registry

Before you edit the registry, export the keys in the registry that you plan to edit, or back up the whole registry. If a problem occurs, you can then follow the steps in the [How to Restore the Registry](#) section of this article to restore the registry to its previous state.

[back to the top](#)

How to Export Registry Keys

You can follow these steps to export a registry key before you edit it:

NOTE: Do not follow these steps to export a whole registry hive (for example, HKEY_CURRENT_USER). If you must back up whole registry hives, back up the whole registry instead.

1. Click **Start**, and then click **Run**.
2. In the **Open** box, type `regedt32`, and then click **OK**.
3. Locate and then click the key that contains the values that you want to edit.
4. On the **Registry** menu, click **Save Key**.
5. In the **Save in** box, select a location in which to save the .reg file, type a file name in the **File name** box, and then click **Save**.

[back to the top](#)

How to Back Up the Whole Registry

To back up the whole registry, use the Backup utility to create an Emergency Repair Disk (ERD), or back up the System State (which includes the registry, the COM+ Class Registration database, and your boot files). For additional information about using the Backup utility to create an ERD, click the article number below to view the article in the Microsoft Knowledge Base:

[231777](#) How to Create an Emergency Repair Disk in Windows 2000

For additional information about using the Backup utility to back up the System State, click the article number below to view the article in the Microsoft Knowledge Base:

[240363](#) HOW TO: Use the Backup Program to Back Up and Restore the System State in Windows 2000

[back to the top](#)

How to Edit the Registry

To edit the registry, Microsoft recommends that you follow the steps in the Microsoft documentation only. If possible, use the Windows user interface instead of directly editing the registry.

Using Registry Editor incorrectly can cause serious problems that may require that you reinstall your operating system. Microsoft cannot guarantee that problems that result from incorrectly using Registry Editor can be solved. Use Registry Editor at your own risk.

For more information about editing the registry, follow these steps in Registry Editor:

1. On the **Help** menu, click **Contents**.
2. On the **Contents** tab, double-click **Registry Editor (Regedt32.exe)**.

3. Double-click the topic that you want to read.

[back to the top](#)

How to Restore the Registry

How to Restore Registry Keys

To restore registry keys that you exported, follow these steps:

1. Click **Start**, and then click **Run**.
2. Type `regedt32`, and then click **OK**.
3. On the **Registry** menu, click **Restore**.
4. Select the file that you saved, and then click **Open**.
5. Click **Yes** to continue.

[back to the top](#)

How to Restore the Whole Registry

To restore the whole registry, restore the System State from a backup. For additional information about using the Backup utility to restore the System State, click the article number below to view the article in the Microsoft Knowledge Base:

[240363](#) HOW TO: Use the Backup Program to Back Up and Restore the System State in Windows 2000

Note that if you use the option to back up the registry when you create an ERD, Backup also creates updated copies of the registry files in the %SystemRoot%\Repair\Regback folder. If you cannot start Windows 2000 after you edit the registry, you can manually replace the registry files in the %SystemRoot%\System32\Config folder with the copies in the %SystemRoot%\Repair\Regback folder by using Recovery Console.

[back to the top](#)

REFERENCES

For additional information, click the article numbers below to view the articles in the Microsoft Knowledge Base:

[240363](#) HOW TO: Use the Backup Program to Back Up and Restore the System State in Windows 2000

[231777](#) How to Create an Emergency Repair Disk in Windows 2000

[back to the top](#)

Keywords: kbHOWTOMaster KB322755

Technology: kbwin2000AdvServ kbwin2000AdvServSearch kbwin2000DataServ kbwin2000DataServSearch kbwin2000Pro kbwin2000ProSearch kbwin2000Search kbwin2000Serv kbwin2000ServSearch kbWinAdvServSearch kbWinDataServSearch

[Send feedback to Microsoft](#)

[© 2004 Microsoft Corporation. All rights reserved.](#)