Knowledge Base

Command-Line Switches for the Microsoft Windows Installer Tool

PSS ID Number: 227091

Article Last Modified on 11/13/2003

The information in this article applies to:

- Microsoft Windows 2000 Server
- Microsoft Windows 2000 Advanced Server
- Microsoft Windows 2000 Professional

This article was previously published under Q227091 For a Microsoft Windows XP version of this article, see <u>314881</u>.

SUMMARY

The Windows Installer executable program that interprets packages and installs products is Msiexec.exe. This article lists the command-line switches for this program. You cannot run the Msiexec.exe program without specifying at least one switch.

MORE INFORMATION

	h Parameters	Description
/i	Package ProductCode	Installs or configures a product.
/f	$\label{eq:pole} \begin{tabular}{ll} $[p o e d c a u m s v]$ Package ProductCode \end{tabular}$	Repairs a product.
		<pre>p - Reinstalls a product only if a file is missing.</pre>
		o - Reinstalls a product if a file is missing or if an older version of a file is installed.
		e - Reinstalls a product if a file is missing or an equal or older version of a file is installed.
		<pre>d - Reinstalls a product if a file is missing or a different version of a file is installed.</pre>
		c - Reinstalls a product if a file is missing or the stored checksum value does not match the calculated value.
		<pre>a - Forces all files to be reinstalled.</pre>
		<pre>u - Rewrites all required user- specific registry entries.</pre>
		<pre>m - Rewrites all required computer-specific registry entries.</pre>
		s - Overwrites all existing shortcuts.
		v - Runs from the source file and re-caches the local package.
/a	Package	Administrative installation option. Installs a product on the network.
/x	Package ProductCode	Uninstalls a product.
/j	$\label{eq:continuity} $$ [u m]Package $$ or $[u m]Package /t Transform List $$ or $[u m]Package /g LanguageID $$ $$$	Advertises a product. The property values used on the command line are ignored.

```
u - Advertises a product
                                                      to the current user.
                                                      m - Advertises a product
                                                      to all users.
                                                      g - Language ID.
                                                      t - Applies a transform
                                                      list to an advertised
                                                      package.
/1
        [i|w|e|a|r|u|c|m|p|v|+|!]Logfile
                                                      Specifies the log
                                                      file path and
                                                      indicates the flags
                                                      to be logged.
                                                      i - Status messages.
                                                      w - Non-fatal warnings.
                                                      e - All error messages.
                                                      a - Startup of actions.
                                                      r - Action-specific
                                                      records
                                                      u - User requests.
                                                      c - Initial User
                                                      Interface (UI)
                                                      parameters
                                                      m - Out-of-memory.
                                                      p - Terminal properties.
                                                      v - Verbose output.
                                                      + - Appends to the
                                                      existing file.
                                                       ! - Clears each line in
                                                      the log file.
                                                       "*" - Wildcard.
                                                      Logs all information,
                                                      but the use of the v
                                                      option is not included
                                                      To include the v option,
                                                      type "/1*v."
                                                      Applies a patch. To
/p Patch/Package
                                                      apply a patch to an
                                                      installed Administrator
                                                      image, type the
                                                      following options:
                                                      /p [PatchPackage]
                                                      /a [Package]
/q n|b|r|f
                                                      Sets the UI level.
                                                      q , qn - No UI.
                                                      qb - Basic UI.
                                                      gr - Reduced UI. A modal
                                                      dialog box is displayed at the end of the
                                                      installation.
                                                      qf - Full UI. A modal
                                                      dialog box is displayed at the end of the
                                                      installation.
                                                      qn+ - No UI. However, a modal dialog box is displayed at the end of
                                                      the installation.
                                                      qb+ - Basic UI. A modal
                                                      dialog box is displayed
                                                      at the end of the installation. If you
                                                      cancel the installation,
                                                      a modal dialog box is
                                                      not displayed.
                                                      qb- - Basic UI with no
                                                      modal dialog boxes.
                                                      The "/qb+-" switch
                                                      is not a supported UI
```

/y module Calls the system Application Programming Interface (API) DllRegisterServer, which registers modules that are typed on the command line (for example, "msiexec /y
my_file.dll"). This option is only used for registry information that cannot be added using the registry tables of the .msi file. /z module Calls the system API DllUnRegisterServer to unregister modules that are typed on the command line (for example, "msiexec /z my_file.dll"). This option is only used for registry information that cannot be removed using the registry tables of the .msi file.

REFERENCES

For more information and examples, please see the "Command Line Options" topic in Windows Installer Help, or visit the following Microsoft Web site:

level.

http://msdn.microsoft.com/library/default.asp?url=/library/en-us/msi/setup/command_line_options.asp

Keywords: kbinfo KB227091

Technology: kbwin2000AdvServ kbwin2000AdvServSearch kbwin2000Pro kbwin2000ProSearch kbwin2000Servkbwin2000Servkbwin2000ServSearch kbwin2000ServSearch kbwin2000Search kbwin2000Search

Send feedback to Microsoft

© 2004 Microsoft Corporation. All rights reserved.