

Tsshutdn

Updated: January 21, 2005

Tsshutdn

Enables an administrator to remotely shut down or reboot a terminal server. You can also choose to power off the server if the computer supports software control of AC power.

Syntax

```
Tsshutdn [WaitTime] [/server:ServerName] [/reboot] [/powerdown] [/delay:LogOffDelay] [/v]
```

Parameters

WaitTime

After notifying users, specifies an amount of time (in seconds) to wait before logging off all users from their sessions. The default is 60 seconds.

/server:ServerName

Specifies the terminal server to shut down. If unspecified, the current terminal server is shut down.

/reboot

Reboots the terminal server after user sessions are ended.

/powerdown

Turns off the terminal server if the computer supports software control of AC power.

/delay:LogOffDelay

After logging off users from their sessions, specifies the amount of time to wait before ending all processes and shutting down the terminal server. The default is 30 seconds.

/v

Displays information about the actions being performed.

/?

Displays help at the command prompt.

Remarks

- You must have administrative credentials to run **tsshutdn**.
- Using **Shut Down** on the **Start** menu is not recommended for shutting down a terminal server. This method does not notify users before ending their sessions.
- All connected sessions are notified that they are going to be shut down. Sessions that have applications with open files prompt the user to save the files. After initiating the logoff command, **tsshutdn** waits a specified interval (the default is 30 seconds, which is set by **/delay**), before ending all processes.
- **Tsshutdn** does not reboot the terminal server unless the **/reboot** option is specified.

Examples

To shut down the computer named TerminalServer1, type:

```
tsshutdn /server:TerminalServer1
```

To reboot the computer named TerminalServer1, type:

tsshutdn /server:TerminalServer1 /reboot

[↑ Top of page](#)

Formatting legend

Format	Meaning
<i>Italic</i>	Information that the user must supply
Bold	Elements that the user must type exactly as shown
Ellipsis (...)	Parameter that can be repeated several times in a command line
Between brackets ([])	Optional items
Between braces ({ }); choices separated by pipe (). Example: {even odd}	Set of choices from which the user must choose only one
Courier font	Code or program output

Related Links

- [Command-line reference A-Z](#)
- [Command shell overview](#)
- [Terminal Services commands](#)
- [Command-line reference](#)

[Manage Your Profile](#)

© 2006 Microsoft Corporation. All rights reserved. [Terms of Use](#) | [Trademarks](#) | [Privacy Statement](#)

Microsoft